


MATERIALS:  
 HEAT SINK:AL  
 CONNECTOR: Cu  
 SUBSTRATE: ALUMINUM NITRIDE  
 FINSH:  
 HEAT SINK: OXIDATION  
 CONNECTOR: ALLOY PLATED ON  
 COPPER BODY  
 TECHNICAL:  
 FREQUENCY RANGE(GHz):DC-8.0  
 OPERATING TEMPERATURE(° C):-55°  
 TO+125°  
 AVERAGE POWER(WATTS):2  
 VSWR: 1.20MAXIMUM  
 RESISTANCE RANGE: 50 OHMS  
 CONNECTOR: SMA TYPE  
 ATTENUATION:3,6,10,15,20,30DB  
 AVAILABLE,AND 1-10dB  
 ± 0.5DB,15-30DB± 1DB

				TOLERANCES				 CENTRON MICROWAVE COMPONENT (SHENZHEN) CO. , LTD.			
				,X± 0.1 ,XX± 0.01      ANGLES X° ±0.1 ,XXX ±0.001				NAME	2W ATTENUATORS	NO.	MANA2SM
				SCALE		REV	A	DRAWING NO		DRAWN	XIE XIANG LONG
REV	DESCRIPTION	DRAWN	APVD	SHEET OF				CHKD		DATE	15.MAY.2009